

Extruded Rifle Powders MATERIAL SAFETY DATA SHEET

January 2011

The following smokeless powders are distributed by Hodgdon Powder Company.

H4227®

H4895®

H4198®

Varget®

H4350®

H50BMG®

H4831®

H4831SC®

H1000®

Retumbo®

H322®

Benchmark®

Issue Date: 2-Apr-2009

C9317EC

CHEMWATCH 4693-84 Version No:2.0 CD 2009/1 Page 1 of 7

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PROPER SHIPPING NAME

POWDER, SMOKELESS

PRODUCT USE

Propellant for use in centrefire ammunition.

SUPPLIER

Company: Thales, Australia, Mulwala

Address: Private Bag 1 Mulwala NSW, 2647 AUS

Company! Thales, Australia, Mulwala Ltd

Address: Bayly Street Mulwala NSW, 2647 AUS

Telephone: +61 2 5742 2200 Emergency Tel: +61 2 5742 2200

Fax: +61 2 5744 1873

Section 2 - HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE

HAZARDOUS SUBSTANCE. DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.

POISONS SCHEDULE

None

RISK

Risk Codes Risk Phrases R01 » Explosive when dry.

» Risk of explosion by shock friction fire or other sources R02

of ignition.

» Heating may cause an explosion.

R20/21/22 » Harmful by inhalation in contact with skin and if

swallowed.

R33 » Danger of cumulative effects.

R45(2) » May cause CANCER.

» Harmful to aquatic organisms may cause long- term adverse effects in the aquatic environment. R52/53

» Possible risk of impaired fertility.

R62(3) » Possible risk of irreversible effects. R68(3)

SAFETY

S13

S60

Safety Phrases Safety Codes S01 » Keep locked up.

» Wear suitable protective clothing. S36

S38 » In case of insufficient ventilation wear suitable

respiratory equipment. S51 » Use only in well ventilated areas.

S401 » To clean the floor and all objects contaminated by this

material use water and detergent.

S35 » This material and its container must be disposed of in a

> » Keep away from food drink and animal feeding stuffs. » This material and its container must be disposed of as

hazardous waste.

Issue Date: 2-Apr-2009 C9317EC

CHEMWATCH 4693-84 Version No:2.0 CD 2009/1 Page 2 of 7

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
nitrocellulose	9004-70-0	>90
2, 4- dinitrotoluene	121-14-2	<10
diphenylamine	122-39-4	0-1
additives		<10

Section 4 - FIRST AID MEASURES

SWALLOWED

- » Not considered a normal route of entry.
- For advice, contact a Poisons Information Centre or a doctor at once.
- Urgent hospital treatment is likely to be needed.
- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration,

- » If this product comes in contact with eyes:
- Wash out immediately with water
- If irritation continues, seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

- » If skin contact occurs:
- Immediately remove all contaminated clothing, including footwear.
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

- » If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.

NOTES TO PHYSICIAN

» Symptoms of vasodilation and reflex tachycardia may present following organic nitrate overdose; most organic nitrates are extensively metabolised by hydrolysis to inorganic nitrites. Organic nitrates and nitrites are readily absorbed through the skin, lungs, mucosa and gastro-intestinal tract. Delayed pulmonary oedema may result following exposure to nitrous oxides formed on thermal decomposition of the propellant.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- » DANGER: Deliver media remotely.
- For minor fires: Flooding quantities only.
- For large fires: Do not attempt to extinguish.

FIRE FIGHTING

- » WARNING: EXPLOSIVE MATERIALS / ARTICLES PRESENT!
- Evacuate all personnel and move upwind.
- Prevent re-entry.
- Alert Fire Brigade and tell them location and nature of hazard.
- May be explosively reactive, detonate and release much heat.

FIRE/EXPLOSION HAZARD

- » WARNING: HIGH EXPLOSION HAZARD!
- Combustible.
- Will burn with rapidly increasing intensity of fire.
- Dry material is extremely sensitive to shock, friction, heat and sparks.
- Avoid metal to metal contact.

FIRE INCOMPATIBILITY

- » Avoid contact with other explosives, pyrotechnics, solvents, adhesives, paints, cleaners and unauthorized metals, plastics, packing equipment and
- Avoid contamination with acids, alkalis, reducing agents, amines and phosphorus.

HAZCHEM: None

Personal Protective Equipment

Gas tight chemical resistant suit.

Limit exposure duration to 1 BA set 30 mins.

Chemwatch Material Safety Data Sheet Issue Date: 2-Apr-2009

C9317EC

CHEMWATCH 4693-84 Version No:2.0 CD 2009/1 Page 3 of 7

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES

MINOR SPILLS

» Clean up all spills immediately.

Avoid contact with skin and eyes.

Wear impervious gloves and safety glasses.

Use spark-free tools when handling.

Remove all ignition sources.

Place spilled material in clean, dry, sealable, labelled container.

Flush spill area with water.

MAJOR SPILLS

» Clear area of personnel.

Restrict access to area.

Alert Fire Brigade and tell them location and nature of hazard.

- May be violently or explosively reactive.

- Wear full body protective clothing with breathing apparatus.

- Prevent, by any means available, spillage from entering drains and water course.

- Consider evacuation (or protect in place).

No smoking or naked lights within area.

Shut off all possible sources of ignition and increase ventilation.

Stop leak if safe to do so.

Environmental hazard - contain spillage.

Collect, using a spark-free shovel, and seal in labelled drums for disposal.

Wash spill area with large quantities of water.

Protective clothing and equipment should be washed down after use and laundered separately from non-contaminated materials.

In the case of a transport accident notify the State Police, State

Explosives Inspector and the Manufacturer, Thales Mulwala Facility.

Collect recoverable packages and segregate from spilled loose material.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

» Use good occupational work practice. Observe manufacturer's storing and handling recommendations.

Avoid all personal contact, including inhalation.

Wear protective clothing when risk of exposure occurs.

Avoid smoking, naked lights, heat or ignition sources.

Must not be struck by metal implements.

Avoid shock and friction

Avoid thermal shock.

Use in a well-ventilated area.

Avoid contact with incompatible materials

When handling, DO NOT eat, drink or smoke

Avoid physical damage to containers

Always wash hands with soap and water after handling. Work clothes should be laundered separately.

SUITABLE CONTAINER

» Check containers are clearly labelled.

- Packaging as recommended by manufacturer.

Explosives Code Packing Instruction P114(b) or 114(b)

General packaging provisions of 4.1.1, 4.1.3 and special provision 4.1.5 are to be met.

For UN 0160, 0161 - If outer packaging is drum then inner packaging is not required.
For UN 0160, 0161 - If outer packaging is 1A2 or 1B2 metal drums then drum construction shall be that risk of explosion, by reason of increase by internal pressure from internal or external causes, is prevented.

For UN 0077, 0132, 0234, 0235, 0236, packagings are to be lead free, otherwise:

Inner Packagings: Bags: Paper Kraft, Plastics, Textiles - sift proof, Woven Plastic - sift proof

Receptacles: Fibreboard, Metal, Paper, Plastic, Woven Plastic - sift proof Intermediate Packagings:

Not necessary

Outer Packagings:

Boxes: Natural Wood (4C1), Natural Wood -sift proof (4C2), Plywood (4D), Reconstituted Wood (4F), Fibreboard (4G)

Drums: Steel, Removable Head (1A2), Aluminium, removable head (1B2), Plywood (1D), Fibre (1G), Plastic, removable head (1H2).

STORAGE INCOMPATIBILITY

- » Segregate from strong acids strong alkalis and strong oxidisers.
- Avoid contact with other explosives, pyrotechnics, solvents, adhesives, paints, cleaners and unauthorized metals, plastics, packing equipment and
- Avoid contamination with acids, alkalis, reducing agents, amines and phosphorus

Chemwatch Material Safety Data Sheet Issue Date: 2-Apr-2009 C9317EC

Benchmark®

CHEMWATCH 4693-84 Version No:2.0 CD 2009/1 Page 4 of 7 Section 7 - HANDLING AND STORAGE

STORAGE REQUIREMENTS

» Store in original containers.

No smoking, naked lights, heat or ignition sources.

Keep dry.

Keep storage area free of debris, waste and combustibles.

Protect containers against physical damage

- Check regularly for spills and leaks.

Store cases in a well ventilated magazine licensed for IMCO class 1.3C

Explosives.

NOTE: If deterioration of the explosive occurs or large quantities of

explosive need to be destroyed notify the Manager, Thales MULWALA Facility or

State Explosives Department.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS Source	Material	TWA mg/m³
Australia Exposure Standards	nitrocellulose (Inspirable dust (not otherwise classified))	10
Australia Exposure Standards	2, 4- dinitrotoluene (Dinitrotoluene (h))	1.5
Australia Exposure Standards	diphenylamine (Diphenylamine)	10

PERSONAL PROTECTION

- » Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants, A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

HANDS/FEET

- » Wear protective gloves, eq. PVC.
- Protective footwear.

OTHER

- » Overalls.
- Eyewash unit.

Ensure ready access to a burns first aid kit.

Manufacture may require: Non-static cleanroom clothing.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required. For further information consult site specific CHEMWATCH data (if available), or your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

» General exhaust is adequate under normal operating conditions. Local exhaust ventilation may be required in specific circumstances.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Dark grey tubules. Bulk density 920 g/L. Insoluble in water. WARNING: SEVERE EXPLOSION HAZARD. Detonation may occur from heavy impact or excessive heating. Avoid all contact with other chemicals.

PHYSICAL PROPERTIES

Does not mix with water.

Sinks in water.

Molecular Weight: Not applicable. Melting Range (℃): Not available. Solubility in water (g/L): Immiscible pH (1% solution): Not applicable. Volatile Component (%vol): Negligible Relative Vapour Density (air=1): Not applicable Lower Explosive Limit (%): Not applicable. Autoignition Temp (℃): 170

Boiling Range (℃): Not available. Specific Gravity (water=1): > 1.0 pH (as supplied): Not applicable Vapour Pressure (kPa): Negligible Evaporation Rate: Not applicable Flash Point (°C): Not applicable Upper Explosive Limit (%): Not applicable. Decomposition Temp (℃): Explosive.

Chemwatch Material Safety Data Sheet Issue Date: 2-Apr-2009 C9317EC

Benchmark®

CHEMWATCH 4693-84 Version No:2.0 CD 2009/1 Page 5 of 7 Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

State: Manufactured

Viscosity: Not Applicable

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- » Product is considered stable under normal handling conditions.
- Stable under normal storage conditions.
- Hazardous polymerization will not occur

For incompatible materials - refer to Section 7 - Handling and Storage

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

» Harmful by inhalation, in contact with skin and if swallowed.

CHRONIC HEALTH EFFECTS » May cause CANCER.

- » Possible risk of impaired fertility. » Danger of cumulative effects.
- » Possible risk of irreversible effects.

TOXICITY AND IRRITATION

» Not available. Refer to individual constituents.

NITROCELLULOSE:

» No significant acute toxicological data identified in literature search.

2,4-DINITROTOLUENE:

» unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

Oral (rat) LD50: 268 mg/kg

Oral (Mouse) LD50: 790 mg/kg

Subcutaneous (Cat) LD: 25 mg/kg

Skin (rabbit): 500 mg/24h - Mild

» The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitls is often characterised by skin redness (erythema) and swelling epidermis.

WARNING: This substance has been classified by the IARC as Group 2B: Possibly Carcinogenic to Humans.

» unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

Oral (Rat) LD50: 1120 mg/kg Oral (Mouse) LD50: 1230 mg/kg

Oral (Guinea) pig: LD50 300 mg/kg

» Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Acute toxicity: Diphenylamine and its substituted derivatives all show a slight to moderate order of toxicity following oral administration, with LD50 values ranging from >500 to > 34,000 mg/kg. Overall, the acute dermal LD50 for these materials was greater than the 2000 mg/kg limit dose indicating a very low order of toxicity.<</>/>.

ADI: 0.02 mg/kg/day NOEL: 1.5 mg/kg/day

CARCINOGEN

2, 4- dinitrotoluene

International Agency for Research on Cancer (IARC) Carcinogens

Group

IRRITATION

2B

SKIN

2, 4- dinitrotoluene

Australia Exposure Standards - Skin

Notes

Sk

Section 12 - ECOLOGICAL INFORMATION

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment This material and its container must be disposed of as hazardous waste.

CHEMWATCH 4693-84 Version No:2.0 CD 2009/1 Page 6 of 7

Section 13 - DISPOSAL CONSIDERATIONS

- » Recycle wherever possible. Special hazards may exist specialist advice may be required.
- Consult manufacturer for recycling options.
 Consult State Land Waste Management Authority for disposal.

- Incinerate residue at an approved site.

Explosives which are surplus, deteriorated or considered unsafe for transport, storage or use shall be destroyed and the statutory authorities shall be notified. Explosive must not be thrown away, buried, discarded or placed with garbage. This material may be disposed of by burning but the operation must be performed under the control of a person competent in the destruction of explosives.

Section 14 - TRANSPORTATION INFORMATION



Labels Required: EXPLOSIVE HAZCHEM: None (ADG7)

Land Transport UNDG:

Class or division: UN No.

1.3C

0161

Subsidiary risk:

None None

None

None

Forbidden

Forbidden

Shipping Name: POWDER, SMOKELESS†

Air Transport IATA:

ICAO/IATA Class: UN/ID Number:

1.3C 0161

Special provisions: Cargo Only

None Forbidden

Earbidden

Packing Instructions: Passenger and Cargo

Packing Instructions:

Passenger and Cargo

Limited Quantity

Packing Instructions:

Shipping Name: POWDER, SMOKELESS †

UN packing group:

ICAO/IATA Subrisk:

Packing Group:

Maximum Qty/Pack:

Passenger and Cargo

Maximum Qty/Pack. Passenger and Cargo

Limited Quantity

Maximum Qty/Pack:

Maritime Transport IMDG:

IMDG Class

1.3C UN Number: 0161 F- B. S- Y EMS Number:

Limited Quantities:

None

Shipping Name: POWDER, SMOKELESS

IMDG Subrisk: Packing Group: Special provisions: None None None

Section 15 - REGULATORY INFORMATION

POISONS SCHEDULE: None

REGULATIONS

BM2 (CAS: None):

No regulations applicable

Regulations for incredients

nitrocellulose (CAS: 9004-70-0) is found on the following regulatory lists;

Australia Dangerous Goods Code (ADG Code) - Goods Too Dangerous To Be Transported

Australia Exposure Standards

Australia High Volume Industrial Chemical List (HVICL)

Australia Inventory of Chemical Substances (AICS) OECD Representative List of High Production Volume (HPV) Chemicals

2,4-dinitrotoluene (CAS; 121-14-2) is found on the following regulatory lists;

Australia Exposure Standards

Australia Hazardous Substances

Australia Inventory of Chemical Substances (AICS) IMO IBC Code Chapter 17: Summary of minimum requirements

IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk International Agency for Research on Cancer (IARC) Carcinogens International Chemical Secretariat (ChemSec) REACH SIN* List (*Substitute It Now!) 1.0 International Council of Chemical Associations (ICCA) - High Production Volume List

OECD Representative List of High Production Volume (HPV) Chemicals

OSPAR List of Substances of Possible Concern

Chemwatch Material Safety Data Sheet Issue Date: 2-Apr-2009

C9317EC

Benchmark®

CHEMWATCH 4693-84 Version No:2.0 CD 2009/1 Page 7 of 7 Section 15 - REGULATORY INFORMATION

diphenylamine (CAS: 122-39-4) is found on the following regulatory lists;

Australia - Australian Capital Territory Environment Protection Regulation Pollutants entering waterways - Domestic water quality

Australia - Victoria Occupational Health and Safety Regulations - Schedule 9: Materials at Major Hazard Facilities (And Their Threshold Quantity)

Table 2

Australia Exposure Standards

Australia Hazardous Substances

Australia Inventory of Chemical Substances (AICS)

Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Appendix E (Part 2) Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Appendix F (Part 3) Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Schedule 6

GESAMP/EHS Composite List of Hazard Profiles - Hazard evaluation of substances transported by ships

IMO Provisional Categorization of Liquid Substances - List 1: Pure or technically pure products OECD Representative List of High Production Volume (HPV) Chemicals

Section 16 - OTHER INFORMATION

» Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net/references.

» The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: 2-Apr-2009 Print Date: 2-Apr-2009

This is the end of the MSDS.