

Extruded Rifle Powders MATERIAL SAFETY DATA SHEET

January 2011

The following smokeless powders are distributed by Hodgdon Powder Company.

H4227®

H4895®

H4198®

Varget®

H4350®

H50BMG®

H4831®

H4831SC®

H1000®

Retumbo®

H322®

Benchmark®

C9317EC

H4350®

CHEMWATCH 4693-51 Version No:2.0 CD 2008/4 Page 1 of 7

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PROPER SHIPPING NAME

POWDER, SMOKELESS†

PRODUCT USE

Propellant for use in centrefire small arms ammunition.

SUPPLIER

Company: Thales, Australia, Mulwala

Address Private Bag 1 Mulwala NSW, 2647 AUS

Company: Thales, Australia, Mulwala Ltd

Address: Bayly Street Mulwala NSW, 2647

AUS

Telephone: +61 2 5742 2200 Emergency Tel: +61 2 5742 2200 Fax: +61 2 5744 1873

Section 2 - HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE

HAZARDOUS SUBSTANCE. DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.

POISONS SCHEDULE

None

RISK

Risk Codes

Risk Phrases

R01 R02 » Explosive when dry. » Risk of explosion by shock friction fire or other sources

of ignition.

R05

» Heating may cause an explosion.

R20/21/22

» Harmful by inhalation in contact with skin and if

swallowed.

R45(2)

» May cause CANCER.

R52/53

» Harmful to aquatic organisms may cause long-term adverse

effects in the aquatic environment. » Possible risk of impaired fertility. » Possible risk of irreversible effects.

R68(3) SAFETY

R62(3)

Safety Codes

Safety Phrases

S01 S36

S38

» Keep locked up.

 » Wear suitable protective clothing.

 » In case of insufficient ventilation wear suitable

respiratory equipment.

S51

» Use only in well ventilated areas.

S401

» To clean the floor and all objects contaminated by this

material use water and detergent.

» This material and its container must be disposed of in a safe way.

S13 **S60**

S35

» Keep away from food drink and animal feeding stuffs. » This material and its container must be disposed of as

hazardous waste.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME nitrocellulose 2, 4- dinitrotoluene additives nonhazardous CAS RN 9004-70-0 121-14-2

% > 85 <10

<10

Section 4 - FIRST AID MEASURES

SWALLOWED

C9317EC

- » For advice, contact a Poisons Information Centre or a doctor at once.
- Urgent hospital treatment is likely to be needed.
- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.

FYF

- » If this product comes in contact with the eyes:
- Immediately hold eyelids apart and flush the eye continuously with running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.
- Transport to hospital or doctor without delay.

SKIN

- » If skin contact occurs:
- Immediately remove all contaminated clothing, including footwear.
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

INHALED

- » If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained.
 Perform CPR if necessary.

NOTES TO PHYSICIAN

» Symptoms of vasodilation and reflex tachycardia may present following organic nitrate overdose; most organic nitrates are extensively metabolised by hydrolysis to inorganic nitrites. Organic nitrates and nitrites are readily absorbed through the skin, lungs, mucosa and gastro-intestinal tract. Delayed pulmonary oedema may result following exposure to nitrous oxides formed on thermal decomposition of the propellant.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- » DANGER: Deliver media remotely.
 - For minor fires: Flooding quantities only.
- For large fires: Do not attempt to extinguish.

FIRE FIGHTING

- » WARNING: EXPLOSIVE MATERIALS / ARTICLES PRESENT!
- Evacuate all personnel and move upwind.
- Prevent re-entry.
- Alert Fire Brigade and tell them location and nature of hazard.
- May be explosively reactive, detonate and release much heat.

FIRE/EXPLOSION HAZARD

- » WARNING: HIGH EXPLOSION HAZARD!
- Combustible.
- Will burn with rapidly increasing intensity of fire.
- Dry material is extremely sensitive to shock, friction, heat and sparks.
- Avoid metal to metal contact.

FIRE INCOMPATIBILITY

- » Avoid contact with other explosives, pyrotechnics, solvents, adhesives, paints, cleaners and unauthorized metals, plastics, packing equipment and materials.
- Avoid contamination with acids, alkalis, reducing agents, amines and phosphorus,

HAZCHEM: None

Personal Protective Equipment

Gas tight chemical resistant suit.

Limit exposure duration to 1 BA set 30 mins.

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES

Chemwatch Material Safety Data Sheet

Issue Date: 6-Mar-2009 C9317EC

H4350®

CHEMWATCH 4693-51 Version No:2.0 CD 2008/4 Page 3 of 7 Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

» Clean up all spills immediately

Avoid contact with skin and eyes

Wear impervious gloves and safety glasses.

Use spark-free tools when handling,

Remove all ignition sources.

Place spilled material in clean, dry, sealable, labelled container.

Flush spill area with water.

MAJOR SPILLS

» Clear area of personnel.

Restrict access to area.

Alert Fire Brigade and tell them location and nature of hazard.

May be violently or explosively reactive.
 Wear full body protective clothing with breathing apparatus.

Prevent, by any means available, spillage from entering drains and water course.
 Consider evacuation (or protect in place).

No smoking or naked lights within area.

Shut off all possible sources of ignition and increase ventilation.

Stop leak if safe to do so.
Environmental hazard - contain spillage.

Collect, using a spark-free shovel, and seal in labelled drums for disposal.

Wash spill area with large quantities of water.

Protective clothing and equipment should be washed down after use and laundered separately from non-contaminated materials.

In the case of a transport accident notify the State Police, State

Explosives Inspector and the Manufacturer, Thales Mulwala Facility

Collect recoverable packages and segregate from loose, spilled material

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

» Use good occupational work practice. Observe manufacturer's storing and handling recommendations.

Avoid all personal contact, including inhalation.

Wear protective clothing when risk of exposure occurs.

Avoid smoking, naked lights, heat or ignition sources.

Must not be struck by metal implements.

Avoid shock and friction.

Avoid thermal shock.

Use in a well-ventilated area.

Avoid contact with incompatible materials.

When handling, DO NOT eat, drink or smoke.

Avoid physical damage to containers.

Always wash hands with soap and water after handling. Work clothes should be laundered separately.

SUITABLE CONTAINER

» Check containers are clearly labelled.- Packaging as recommended by manufacturer.

- Packaging as recommended by manufacture.

Explosives Code Packing Instruction P114(b) or 114(b)

General packaging provisions of 4.1.1, 4.1.3 and special provision 4.1.5 are to be met.

For UN 0160, 0161 - If outer packaging is drum then inner packaging is not required.

For UN 0160, 0161 - If outer packaging is 1A2 or 1B2 metal drums then drum construction shall be that risk of explosion, by reason of increase by internal pressure from internal or external causes, is prevented.

For UN 0077, 0132, 0234, 0235, 0236, packagings are to be lead free, otherwise:

Inner Packagings:

Bags: Paper Kraft, Plastics, Textiles - sift proof, Woven Plastic - sift proof

Receptacles: Fibreboard, Metal, Paper, Plastic, Woven Plastic - sift proof

Intermediate Packagings:

Not necessary

Outer Packagings:

Boxes: Natural Wood (4C1), Natural Wood -sift proof (4C2), Plywood (4D), Reconstituted Wood (4F), Fibreboard (4G)

Drums: Steel, Removable Head (1A2), Aluminium, removable head (1B2), Plywood (1D), Fibre (1G), Plastic, removable head (1H2).

STORAGE INCOMPATIBILITY

» Segregate from strong acids strong alkalis and strong oxidisers.

- Avoid contact with other explosives, pyrotechnics, solvents, adhesives, paints, cleaners and unauthorized metals, plastics, packing equipment and
- Avoid contamination with acids, alkalis, reducing agents, amines and phosphorus.

STORAGE REQUIREMENTS

- » Store in original containers.
- Keep containers securely sealed.
- Store in a cool, dry area protected from environmental extremes.
- Store away from incompatible materials and foodstuff containers.

Store in original containers.

No smoking, naked lights, heat or ignition sources.

Keep dry.

Chemwatch Material Safety Data Sheet Issue Date: 6-Mar-2009

C9317EC

H4350®

CHEMWATCH 4693-51 Version No:2.0 CD 2008/4 Page 4 of 7 Section 7 - HANDLING AND STORAGE

Keep storage area free of debris, waste and combustibles.

Protect containers against physical damage.

- Check regularly for spills and leaks.

Store cases in a well ventilated magazine licensed for IMCO class 1.3C

Explosives.

NOTE: If deterioration of the explosive occurs or large quantities of

explosive need to be destroyed notify the Manager, Thales Mulwala Facility or

State Explosives Department.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

Source

Material

TWA mg/m³

Australia Exposure Standards

nitrocellulose (Inspirable dust (not

10

Australia Exposure Standards

otherwise classified)) 2, 4- dinitrotoluene (Dinitrotoluene

1.5

PERSONAL PROTECTION

RESPIRATOR

Particulate

EYE

- » Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

HANDS/FEET

- » Wear protective gloves, eg. PVC.
- Protective footwear.

OTHER

- » Overalls.
- Eyewash unit.

Ensure ready access to a burns first aid kit.

Impervious apron.

Ensure there is ready access to a safety shower.

- Barrier cream.

Manufacture may require:

Non-static clean room clothing

ENGINEERING CONTROLS

» General exhaust is adequate under normal operating conditions. Local exhaust ventilation may be required in specific circumstances.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Dark grey tubules.

Bulk density range 850-950 g/L. Insoluble in water.
WARNING: SEVERE EXPLOSION HAZARD. Detonation may occur from heavy impact

or excessive heating. Avoid all contact with other chemicals.

PHYSICAL PROPERTIES

Solid.

Does not mix with water.

Sinks in water.

Molecular Weight: Not applicable. Melting Range (℃): Not available. Solubility in water (g/L): Immiscible pH (1% solution): Not applicable. Volatile Component (%vol): Negligible Relative Vapour Density (air=1): Not applicable Lower Explosive Limit (%): Not applicable. Autoignition Temp (°C): 170

Boiling Range (℃): Not available. Specific Gravity (water=1): > 1 approx pH (as supplied): Not applicable Vapour Pressure (kPa): Negligible Evaporation Rate: Not applicable Flash Point (℃): Not applicable Upper Explosive Limit (%): Not applicable. Decomposition Temp (℃): Explosive.

Chemwatch Material Safety Data Sheet Issue Date: 6-Mar-2009

C9317EC

H4350®

CHEMWATCH 4693-51 Version No:2.0 CD 2008/4 Page 5 of 7 Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

State:	Divided	enlid
Glate.	DINIGEO	SUIIU

Viscosity: Not Applicable

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- » Product is considered stable under normal handling conditions.
- Stable under normal storage conditions
- Hazardous polymerization will not occur.

For incompatible materials - refer to Section 7 - Handling and Storage.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

» Harmful by inhalation, in contact with skin and if swallowed.

CHRONIC HEALTH EFFECTS

- » May cause CANCER.
- » Possible risk of impaired fertility.
- » Possible risk of irreversible effects.
- » Cumulative effects may result following exposure*.
- » Possible respiratory and skin sensitiser*.
- » * (limited evidence).

TOXICITY AND IRRITATION

» Not available. Refer to individual constituents.

NITROCELLULOSE:

» No significant acute toxicological data identified in literature search.

» unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

Oral (rat) LD50: 268 mg/kg Oral (Mouse) LD50: 790 mg/kg IRRITATION

Skin (rabbit): 500 mg/24h - Mild

Oral (Mouse) LUGO. 1750 Highly Subcutaneous (Cat) LD: 25 mg/kg

Subcutaneous (Cat) LD: 25 mg/kg

» The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling epidemis.

WARNING: This substance has been classified by the IARC as Group 2B: Possibly Carcinogenic to Humans.

CARCINOGEN

2, 4- dinitrotoluene

International Agency for Research on Cancer (IARC) Carcinogens

Group

2B

SKIN

2, 4- dinitrotoluene

Australia Exposure Standards - Skin

Notes

Sk

Section 12 - ECOLOGICAL INFORMATION

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. This material and its container must be disposed of as hazardous waste.

Section 13 - DISPOSAL CONSIDERATIONS

- » Recycle wherever possible. Special hazards may exist specialist advice may be required.
- Consult manufacturer for recycling options
- Consult State Land Waste Management Authority for disposal.
- Incinerate residue at an approved site.

Explosives which are surplus, deteriorated or considered unsafe for transport, storage or use shall be destroyed and the statutory authorities shall be notified. Explosive must not be thrown away, buried, discarded or placed with garbage. This material may be disposed of by burning but the operation must be performed under the control of a person competent in the destruction of explosives.

Section 14 - TRANSPORTATION INFORMATION



C9317EC

Labels Required: EXPLOSIVE HAZCHEM: None (ADG7)

Land Transport UNDG:

Class or division: 1.3C UN No.: 0161

Shipping Name: POWDER, SMOKELESS†

Air Transport IATA:

ICAO/IATA Class: 1.3C UN/ID Number: 0161 Special provisions: None

Cargo Only Packing Instructions:

Passenger and Cargo

Packing Instructions: Passenger and Cargo

Limited Quantity Packing Instructions:

Shipping Name: POWDER, SMOKELESS †

Maritime Transport IMDG:

IMDG Class: 1.3C UN Number: 0161 EMS Number: F-B, S-Y Limited Quantities: None

Shipping Name: POWDER, SMOKELESS

Subsidiary risk: UN packing group:

ICAO/IATA Subrisk: Packing Group:

Maximum Qty/Pack: Passenger and Cargo Maximum Qty/Pack:

Passenger and Cargo Limited Quantity Maximum Qty/Pack:

IMDG Subrisk:

Packing Group: Special provisions: None None None

None

None

None

None

Forbidden

Forbidden

Section 15 - REGULATORY INFORMATION

Forbidden

Forbidden

POISONS SCHEDULE: None

REGULATIONS

Regulations for ingredients ADI Sporting Powder AR 2209 (CAS: None): No regulations applicable

nitrocellulose (CAS: 9004-70-0) is found on the following regulatory lists;
Australia Dangerous Goods Code (ADG Code) - Goods Too Dangerous To Be Transported

Australia Exposure Standards

Australia High Volume Industrial Chemical List (HVICL)

Australia Inventory of Chemical Substances (AICS)

OECD Representative List of High Production Volume (HPV) Chemicals

2,4-dinitrotoluene (CAS: 121-14-2) is found on the following regulatory lists;

Australia Exposure Standards Australia Hazardous Substances

Australia Inventory of Chemical Substances (AICS)

IMO IBC Code Chapter 17: Summary of minimum requirements

IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk International Agency for Research on Cancer (IARC) Carcinogens International Chemical Secretariat (ChemSec) REACH SIN* List (*Substitute It Now!) 1.0

International Council of Chemical Associations (ICCA) - High Production Volume List

OECD Representative List of High Production Volume (HPV) Chemicals OSPAR List of Substances of Possible Concern

Section 16 - OTHER INFORMATION

» Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references. A list of reference resources used to assist the committee may be found at: www.chemwatch.net/references.

» The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written

Chemwatch Material Safety Data Sheet Issue Date: 6-Mar-2009 C9317EC

H4350®

CHEMWATCH 4693-51 Version No:2.0 CD 2008/4 Page 7 of 7 Section 16 - OTHER INFORMATION

permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: 6-Mar-2009 Print Date: 6-Mar-2009

This is the end of the MSDS.